

AUG-JP線種

::

:: Linetype Definition related to JIS Z 8312

:: Autodesk User Group Japan (AUG-JP)

::

::一点鎖線

*JIS_08_11,1SASEN11 _ _ _ _ _

A,11,-.60,.60,-.60

*JIS_08_15,1SASEN15 _ _ _ _ _

A,15,-.75,.75,-.75

*JIS_08_25,1SASEN25 _ _ _ _ _

A,25,-1.125,.75,-1.125

*JIS_08_37,1SASEN37 _ _ _ _ _

A,37.5,-1.125,.75,-1.125

*JIS_08_50,1SASEN50 _ _ _ _ _

A,50,-1.125,.75,-1.125

::破線

*JIS_02_0.7,HIDDEN0.75 _ _ _ _ _

A,.75,-.60

*JIS_02_1.0,HIDDEN01 _ _ _ _ _

A,1,-1

*JIS_02_1.2,HIDDEN01.25 _ _ _ _ _

A,1.25,-1.25

*JIS_02_2.0,HIDDEN02 _ _ _ _ _

A,2,-1

*JIS_02_4.0,HIDDEN04 _ _ _ _ _

A,4,-1.5

::二点鎖線

*JIS_09_08,2SASEN8 _ _ _ _ _

A,8,-.55,.55,-.55,.55,-.55

*JIS_09_15,2SASEN15 _ _ _ _ _

A,15,-.90,.60,-.90,.60,-.90

*JIS_09_29,2SASEN29 _ _ _ _ _

A,29,-1.2,.70,-1.2,.70,-1.2

*JIS_09_50,2SASEN50 _ _ _ _ _

A,50,-1.2,.70,-1.2,.70,-1.2
